

**METHODS OF ANALYZING POLYMERS USING ORDERED LABEL****STRATEGIES****Related Applications**

This application claims priority to U.S. Provisional Patent Application Nos.

5 60/096,666, filed August 13, 1998 and 60/096,662, filed August 13, 1998 and is a  
continuation in part of U.S. Patent Serial No. 09/134,411 filed on August 13, 1998, currently  
pending, which is a continuation of PCT/US98/03024 filed on February 11, 1998, which  
claims priority to U.S. Provisional Patent Application Nos. 60/064,687, filed May 5, 1997 and  
60/037,921, filed February 11, 1997 the entire contents of which are hereby incorporated by  
10 reference.

**Field Of The Invention**

The present invention relates to methods and products for analyzing polymers. In particular,  
the methods are based on generation of information from a data set of polymer dependent  
impulses arising from polymers which have been labeled according to an ordered strategy.

15 The information generated relates to many aspects of the polymer such as the length of the  
polymer, the composition of units within the polymer, the order of units in the polymer, and  
the sequence or partial sequence of units in the polymer. The invention also relates to  
methods for intensity based analysis.

**Background Of The Invention**

20 Polymers are involved in diverse and essential functions in living systems. The ability  
to decipher the function of polymers in these systems is integral to the understanding of the  
role that the polymer plays within a cell. Often the function of a polymer in a living system is  
determined by analyzing the structure and determining the relation between the structure and  
the function of the polymer. By determining the primary sequence in a polymer such as a  
25 nucleic acid it is possible to generate expression maps, to determine what proteins are  
expressed, and to understand where mutations occur in a disease state. Because of the wealth  
of knowledge that may be obtained from sequencing of polymers many methods have been  
developed to achieve more rapid and more accurate sequencing methods.

In general DNA sequencing is currently performed using one of two methods. The  
30 first and more popular method is the dideoxy chain termination method described by Sanger  
et al. (1977). This method involves the enzymatic synthesis of DNA molecules terminating in  
dideoxynucleotides. By using the four ddNTPs, a population of molecules terminating at

each position of the target DNA can be synthesized. Subsequent analysis yields information on the length of the DNA molecules and the base at which each molecule terminates (either A, C, G, or T). With this information, the DNA sequence can be determined. The second method is Maxam and Gilbert sequencing (Maxam and Gilbert, 1977), which uses chemical degradation to generate a population of molecules degraded at certain positions of the target DNA. With knowledge of the cleavage specificities of the chemical reactions and the lengths of the fragments, the DNA sequence is generated. Both methods rely on polyacrylamide gel electrophoresis and photographic visualization of the radioactive DNA fragments. Each process takes about 1-3 days. The Sanger sequencing reactions can only generate 300-800 bases in one run.

Methods to improve the output of sequence information using the Sanger method also have been proposed. These Sanger-based methods include multiplex sequencing, capillary gel electrophoresis, and automated gel electrophoresis. Recently, there has also been increasing interest in developing Sanger independent methods as well. Sanger independent methods use a completely different methodology to realize the base information. This category includes scanning electron microscopy (STM), mass spectrometry, enzymatic luminometric inorganic pyrophosphate detection assay (ELIDA) sequencing, exonuclease sequencing, and sequencing by hybridization.

Further, several new methods have been described for carboxy terminal sequencing of polypeptides. See Inglis, A. S., *Anal. Biochem.* 195:183-96 (1991). Carboxy terminal sequencing methods mimic Edman degradation but involve sequential degradation from the opposite end of the polymer. See Inglis, A. S., *Anal. Biochem.* 195:183-96 (1991). Like Edman degradation, the carboxy-terminal sequencing methods involve chemically induced sequential removal and identification of the terminal amino acid residue.

More recently, polypeptide sequencing has been described by preparing a nested set (sequence defining set) of polymer fragments followed by mass analysis. See Chait, B. T. et al., *Science* 257:1885-94 (1992). Sequence is determined by comparing the relative mass difference between fragments with the known masses of the amino acid residues. Though formation of a nested (sequence defining) set of polymer fragments is a requirement of DNA sequencing, this method differs substantially from the conventional protein sequencing method consisting of sequential removal and identification of each residue. Although this

method has potential in practice it has encountered several problems and has not been demonstrated to be an effective method.

### **Summary Of The Invention**

The present invention relates in some aspects to methods and products for analyzing  
5 polymers. In particular the invention in one aspect is a method for identifying information about a polymer such as its sequence, length, order of bases etc., by obtaining polymer dependent impulses from a population of polymers and comparing the polymer dependent impulses to determine unit specific information about the polymers.

Recently, methods for analyzing polymers based on unit specific information about  
10 the polymer have been developed. Such methods are described in co-pending PCT patent application No. PCT/US98/03024 and US Serial No. 09/134,411 filed August 13, 1998, the entire contents of which are hereby incorporated by reference. The method for analyzing polymers described in PCT/US98/03024 and 09/134,411 is based on the ability to examine each unit or unit specific marker of a polymer individually. By examining each unit or unit specific  
15 marker individually the type of units and the position of the units on the backbone of the polymer can be identified. This can be accomplished by positioning a labeled unit or unit specific marker at a station and examining a change which occurs when that labeled unit or unit specific marker is proximate to the station. The change can arise as a result of an interaction that occurs between the unit or unit specific marker and the station or a partner and  
20 is specific for the particular unit or unit specific marker. For instance if the polymer is a nucleic acid molecule and a T is positioned in proximity to a station a change which is specific for a T could occur. If on the other hand, a G is positioned in proximity to a station then a change which is specific for a G could occur. The specific change which occurs, for example, depends on the station used, the type of polymer being studied and/or the label used.  
25 For instance the change may be an electromagnetic signal which arises as a result of the interaction.

Methods for analyzing polymers based on unit specific information about the polymer involves the detection of polymer dependent impulses from a plurality of polymers to produce a data set of information. The data set can be compared to provide specific information about  
30 the polymer such as the composition of units in the polymer, the length of the polymer, the presence of specific sequences in the polymer, and even the entire sequence of the units in the polymer.

In one aspect the invention is a method for generating unit specific information about a polymer. The method includes the steps of obtaining polymer dependent impulses for a plurality of labeled polymers, comparing the polymer dependent impulses obtained from each of the plurality of labeled polymers, determining unit specific information about the polymers based upon comparing the polymer dependent impulses. Preferably the polymer dependent impulses arise from unit specific markers of less than all units of the polymers. In an embodiment the polymer dependent impulses arise from at least two unit specific markers of the polymers.

The plurality of polymers may be any type of polymer but preferably is a nucleic acid.

10 In one embodiment the plurality of polymers is a homogenous population. In another embodiment the plurality of polymers is a heterogenous population. The polymers can be labeled, randomly or non randomly. Different labels can be used to label different linked units to produce different polymer dependent impulses.

The polymer dependent impulses provide many different types of structural  
15 information about the polymer. For instance the obtained polymer dependent impulses may include an order of polymer dependent impulses or the obtained polymer dependent impulses may include the time of separation between specific signals or the number of specific polymer dependent impulses. The obtained polymer dependent impulses may indicate the sequence of units of the polymer.

20 In one important embodiment the polymer dependent impulses are obtained by moving the plurality of polymers linearly past a signal generation station.

According to another embodiment the unit specific markers are nucleic acid probes. In another embodiment the unit specific markers are peptide nucleic acid probes.

The unit specific markers may identify a single unit of a polymer or multiple units of a  
25 polymer. When the polymer is a nucleic acid the unit specific marker may be a nucleic acid probe. In one embodiment the unit specific marker is a nucleic acid probe having at least two base pairs. In another embodiment the unit specific marker is a nucleic acid probe having at least three base pairs.

According to another aspect of the invention a method for sequencing a polymer of  
30 linked units is provided. The method includes the steps of obtaining polymer dependent impulses from a plurality of overlapping polymers, at least a portion of each of the polymers having a sequence of linked units identical to the other of the polymers, and comparing the

polymer dependent impulses from an overlapping portion of each of the plurality of polymers to obtain a sequence of linked units which is identical in the plurality of polymers.

The polymer dependent impulses may be detected by many means. A preferred method of detection is optical detection.

- 5           The plurality of polymers may be any type of polymer but preferably is a nucleic acid. Preferably the nucleic acids are labeled with an agent selected from the group consisting of an electromagnetic radiation source, a quenching source and a fluorescence excitation source. In one embodiment the plurality of polymers is a homogenous population. In another embodiment the plurality of polymers is a heterogenous population. The polymers can be  
10   labeled, randomly or non randomly. Different labels can be used to label different linked units to produce different polymer dependent impulses.

- The polymer dependent impulses provide many different types of structural information about the polymer. For instance the obtained polymer dependent impulses may include an order of polymer dependent impulses or the obtained polymer dependent impulses  
15   may include the time of separation between specific signals or the number of specific polymer dependent impulses. The obtained polymer dependent impulses may indicate the sequence of units of the polymer.

In one important embodiment the polymer dependent impulses are obtained by moving the plurality of polymers linearly past a signal generation station.

- 20           According to another embodiment the unit specific marker is a nucleic acid probe. In another embodiment the unit specific markers is a peptide nucleic acid probe. In another embodiment, the unit specific marker is a peptide.

- The unit specific markers may identify a single unit of a polymer or multiple units of a polymer. When the polymer is a nucleic acid the unit specific marker may be a nucleic acid  
25   probe. In one embodiment the unit specific marker is a nucleic acid probe having at least three base pairs. In another embodiment the unit specific markers are three base pair nucleic acid probes.

- The invention in another aspect is a kit for labeling polymers. The kit includes a container housing a series of distinct nucleic acid probes; wherein the series of nucleic acid  
30   probes is a set of multiple base pair probes. Preferably the multiple base pair probes are selected from the group consisting of two base pair probes, three base pair probes, four base pair probes, and five base pair probes.

In one embodiment the container is a single container having a plurality of compartments, each housing a specific labeled probe. In another embodiment the container is a plurality of containers.

5 The kit in one embodiment also includes instructions for labeling the nucleic acid probes.

The distinct nucleic acid probes are labeled in one embodiment. Preferably the nucleic acid probes are labeled with an agent selected from the group consisting of an electromagnetic radiation source, a quenching source and a fluorescence excitation source. In one embodiment the plurality of polymers is a homogenous population. In another  
10 embodiment the distinct nucleic acid probes are three base pair probes. In another embodiment the distinct nucleic acid probes are four base pair probes. In yet another embodiment the distinct nucleic acid probes are five base pair probes.

The invention in other aspects relates to methods and products for linear analysis of polymers using an intensity based method for identifying information about the polymer such  
15 as its sequence, length, order of bases etc. The methods can be accomplished using intensity based measurements combined with the ordered labeling strategy discussed above.

One aspect of linear analysis involves the movement of the polymer past a fixed station in such a manner as to cause a signal that provides information about the polymer to arise. According to an aspect of the invention it was discovered that information about the  
20 polymer can be determined by quantitatively measuring intensity of the signal arising at the station. The signal arises from the polymer as a result of the units of the polymer passing the fixed station. In some cases all of the units may cause the generation of a signal and in other cases less than all of the units produce the signal. The total intensity of the signal is proportional to the number of units or unit specific markers which generate a signal as they  
25 pass the fixed station. If the signal arises from every unit of the polymer then the intensity of the signal is proportional to the number of units in the polymer. If the signal arises from less than all of the units or unit specific markers of the polymer then the intensity of the signal is proportional to that number of units or unit specific markers causing generation of the signal. The number of units or unit specific markers indicated by the intensity can be used to  
30 determine information about the polymer such as the composition of units in the polymer, the length of the polymer, the presence of specific sequences in the polymer, and even the entire sequence of the units in the polymer.

The invention in another aspect is a method for analyzing a polymer by linearly moving a labeled polymer with respect to a fixed station, obtaining a signal from the labeled polymer as the labeled polymer passes the fixed station, wherein the signal is an electromagnetic radiation signal arising from an interaction between at least two distinct labeled unit specific markers and determining a quantitative measure of intensity of the signal to analyze the polymer.

The intensity of the signal provides various types of structural information about a polymer, depending on how the polymer is labeled. In one embodiment each unit of the labeled polymer is labeled with a unit specific marker and the quantitative measure of intensity of the signal indicates the length of the polymer. In another embodiment less than all units of the polymer are labeled with at least one unit specific marker and the quantitative measure of intensity of the signal indicates the number of labeled unit specific markers present in the polymer.

The fixed station which gives rise to the signal when the labeled polymer interacts with the station in one embodiment is an electromagnetic radiation source. In another embodiment the fixed station is a radiation source.

More than one polymer may be analyzed to generate a data set representative of a population of polymers. Thus in one embodiment a plurality of polymers are analyzed simultaneously to produce a plurality of signals, one signal for each polymer, and further comprising the step of comparing the intensities of the signals to analyze the polymers.

The labeled polymer may be labeled with a unit specific marker. In one embodiment the unit specific marker is a peptide nucleic acid probe. In another embodiment the unit specific marker is a series of distinct nucleic acid probes selected from the group consisting of two base pair probes, three base pair probes, four base pair probes, and five base pair probes. In yet another embodiment the unit specific marker is a fluorescent probe.

According to another embodiment the labeled polymer is labeled with a plurality of unit specific markers, wherein at least one unit specific marker includes a fluorophore which emits light at a first wavelength and at least one unit specific marker which includes a fluorophore which emits light at a second wavelength. In another embodiment the at least one unit specific marker which includes the fluorophore which emits light at the first wavelength is attached to end units of the polymer and wherein the at least one unit specific

marker which emits light at the second wavelength is attached to an internal unit of the polymer.

Each of the limitations of the invention can encompass various embodiments of the invention. It is, therefore, anticipated that each of the limitations of the invention involving  
5 any one element or combinations of elements can be included in each aspect of the invention.

### **Brief Description Of The Drawings**

Figure 1 shows a schematic of a random labeling method in which two differently labeled DNA samples are used.

Figure 2 is a graph of raw data demonstrating changes in energy emission patterns to  
10 determine distance information through the instantaneous rate method. The changes in energy patterns result from sequential detectable signals which when plotted produce a curve that from left to right shows two energy intensity decreases, followed by two energy intensity increases. The rate is 6.8 A/s and  $t_1$  is the time between the entry of the first and second labels.

15 Figure 3 shows a schematic of a random labeling method using a one nucleotide labeling scheme where less than all of the one nucleotide are labeled.

Figure 4 shows a schematic of a random labeling method using a two nucleotide labeling scheme.

Figure 5 shows a schematic of a random labeling method using two differently labeled  
20 nucleic acid samples.

Figure 6 illustrates the generation of sequence information from the sorted data.

Figure 7 illustrates the labeling of unit specific markers with more than one type of label.

Figure 8 shows a schematic of a random labeling method using triplet unit specific  
25 markers one of which is kept constant during the analysis.

Figure 9 shows a schematic of a random labeling method of a double stranded nucleic acid analysis using direction specific labels.

Figure 10 is a sample kit according to the invention.

Figure 11A is a schematic representation of a labeled DNA molecule moving through  
30 a nanochannel plate and 11B is a fluorescence illumination graph from which intensity can be determined.



Figure 12A is a schematic diagram of a waveguide structure with a labeled DNA molecule passing through it and 12B is similar to 11B.

Figure 13 is a schematic diagram of a hexagonally packed bead nanostructure for analyzing polymers.

5                                    **Brief Description Of The Sequences**

SEQ. ID. NO. 1 is a hypothetical nucleic acid sequence.

SEQ. ID. NO. 2 is a hypothetical nucleic acid sequence.

SEQ. ID. NO. 3 is a hypothetical nucleic acid sequence.

**Detailed Description Of The Invention**

10            The invention is a method for analyzing polymers based on a compilation of data obtained from incomplete labeling of the polymers. The methods can be performed using data generated from single unit labels or multiple unit labels (both referred to herein as unit specific markers), single stranded polymers, double stranded polymers, or combinations thereof.

15            One advantage of the invention is that the method provides a rational means of deciphering incomplete labeling schemes into information, e.g., sequence information about the polymer, without requiring the labeling of each unit within a polymer. There are certain physical limits to labeling polymers such as DNA, which make it very difficult to completely label every nucleotide in a strand of DNA. For instance, in a single strand of DNA, the  
20 replacement of the native bases by fluorescently labeled bases is hindered by the major groove and base-to-base steric interactions of fluorophores derivatized to adjacent bases. Stack hindrance problems have made common methods of DNA analysis such as exonuclease sequencing difficult to perform. The methods of the invention provide the ability to decipher incomplete labeling schemes through various labeling methods to generate sequence  
25 information about polymers rapidly and accurately. The methods of the invention also provide enhanced resolution over prior art sequencing methods.

              In one aspect the invention is a method for generating unit specific information about a polymer. The method includes the steps of obtaining polymer dependent impulses for a plurality of labeled polymers, comparing the polymer dependent impulses of the plurality of  
30 labeled polymers, determining unit specific information about the polymers based upon the polymer dependent impulses. Preferably the polymer dependent impulses arise from unit specific markers of less than all units of the polymers.

As used herein the term "unit specific information" refers to any structural information about one, some, or all of the units of the polymer. The structural information obtained by analyzing a polymer according to the methods of the invention may include the identification of characteristic properties of the polymer which (in turn) allows, for example, for the  
5 identification of the presence of a polymer in a sample or a determination of the relatedness of polymers, identification of the size of the polymer, identification of the proximity or distance between two or more individual units or unit specific markers a polymer, identification of the order of two or more individual units or unit specific markers within a polymer, and/or identification of the general composition of the units or unit specific markers of the polymer.  
10 Since the structure and function of biological molecules are interdependent, the structural information can reveal important information about the function of the polymer.

The methods of the invention are performed by detecting signals referred to as polymer dependent impulses. A "polymer dependent impulse" as used herein is a detectable physical quantity which transmits or conveys information about the structural characteristics  
15 of a unit specific marker of a polymer. The physical quantity may be in any form which is capable of being detected. For instance the physical quantity may be electromagnetic radiation, chemical conductance, electrical conductance, etc. The polymer dependent impulse may arise from energy transfer, quenching, changes in conductance, radioactivity, mechanical changes, resistance changes, or any other physical changes. Although the polymer dependent  
20 impulse is specific for a particular unit specific marker, a polymer having more than one of a particular labeled unit specific marker will have more than one identical polymer dependent impulse. Additionally, each unit specific marker of a specific type may give rise to different polymer dependent impulses if they have different labels. In some embodiments when intensity of a signal is being measured, the polymer dependent impulse is an optical signal

25 The method used for detecting the polymer dependent impulse depends on the type of physical quantity generated. For instance if the physical quantity is electromagnetic radiation then the polymer dependent impulse is optically detected. An "optically detectable" polymer dependent impulse as used herein is a light based signal in the form of electromagnetic radiation which can be detected by light detecting imaging systems. In some embodiments  
30 the intensity of this signal is measured. When the physical quantity is chemical conductance then the polymer dependent impulse is chemically detected. A "chemically detected" polymer dependent impulse is a signal in the form of a change in chemical concentration or

charge such as an ion conductance which can be detected by standard means for measuring chemical conductance. If the physical quantity is an electrical signal then the polymer dependent impulse is in the form of a change in resistance or capacitance.

A "plurality of polymers" is at least two polymers. A plurality of polymers in one  
5 embodiment is at least 50 polymers and in another embodiment is at least 100 polymers.

The polymer dependent impulses may provide any type of structural information about the polymer. For instance these signals may provide the entire or portions of the entire sequence of the polymer, the order of polymer dependent impulses, or the time of separation between polymer dependent impulses as an indication of the distance between the units or  
10 unit specific markers.

The polymer dependent impulse arises from a detectable physical change in the unit specific marker of the polymer or the station (or environment surrounding the station). As used herein a "detectable physical change" in the unit specific marker of the polymer or the station is any type of change which occurs in the unit specific marker of the polymer or the  
15 station as a result of exposing the unit specific marker to the station. Once the unit specific marker is exposed to the station a detectable signal or polymer dependent impulse is created. The station may be for instance, an interaction station or a signal generation station. The type of change that occurs in the station or the unit specific marker to produce the detectable signal or polymer dependent impulse depends on the type of station and the type of unit specific  
20 marker. Several examples of station-unit specific marker combinations which undergo a change to produce a detectable signal are discussed herein for exemplary purposes. Those of skill in the art will be able to derive other station-unit specific marker combinations that fall within the scope of the invention.

The polymer dependent impulses are obtained by interaction which occurs between  
25 the unit specific marker of the polymer and a signal generation station or the environment at a signal generation station. A "signal generation station" as used herein is a station that is an area where the unit specific marker interacts with the station or the environment to generate a polymer dependent impulse. In some aspects of the invention the polymer dependent impulse results from contact in a defined area with an agent selected from the group consisting of  
30 electromagnetic radiation, a quenching source, and a fluorescence excitation source which can interact with the unit specific marker to produce a detectable signal or polymer dependent impulse. In other aspects the polymer dependent impulse results from contact in a defined

area with a chemical environment which is capable of undergoing specific changes in conductance in response to an interaction with a molecule. As a molecule with a specific structure interacts with the chemical environment a change in conductance occurs. The change which is specific for the particular structure may be a temporal change, e.g., the length of time required for the conductance to change may be indicative that the interaction involves a specific structure or a physical change. For instance, the change in intensity of the interaction may be indicative of an interaction with a specific structure. In other aspects the polymer dependent impulse results from changes in capacitance or resistance caused by the movement of the unit specific marker between microelectrodes or nanoelectrodes positioned adjacent to the polymer unit specific marker. For instance the signal generation station may include microelectrodes or nanoelectrodes positioned on opposite sides of the polymer unit specific marker. The changes in resistance or conductance which occur as a result of the movement of the unit specific marker past the electrodes will be specific for the particular unit specific marker.

The invention also relates to a method of analyzing polymers using linear analysis to generate an optical signal, wherein the intensity of the optical signal provides information about the polymer to analyze the polymer. The generated optical signal may be any type of electromagnetic radiation signal for which intensity can be determined (e.g., fluorescence, radiation, etc.).

As used herein "similar polymers" are polymers which have at least one overlapping region. Similar polymers may be a homogeneous population of polymers or a heterogenous population of polymers. A "homogeneous population" of polymers as used herein is a group of identical polymers. A "heterogenous population" of similar polymers is a group of similar polymers which are not identical but which include at least one overlapping region of identical units. An overlapping region typically consists of at least 10 contiguous nucleotides. In some cases an overlapping region consists of at least 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, or 22 contiguous nucleotides.

A "plurality of labeled polymers" refers to two or more similar polymers which are labeled intrinsically or extrinsically. Preferably a plurality of similar polymers is 50 or more similar polymers. More preferably a plurality of similar polymers is 100 or more similar polymers.

A "data set" as used herein is a set of information defining the polymer dependent impulses generated by similar polymers. The data set is analyzed as discussed above and the method of analysis used depends on the type of labeling scheme used to generate the labeled polymers.

5 Nucleic acid sequencing is a particularly preferred embodiment of the methods of the invention. Currently, less than 5% of the human genome has been sequenced. This translates into a small fraction of the ideal in human sequence knowledge, which is the sequence of all individuals. For instance, for the human population, there are  $1.4 \times 10^{19}$  (5 billion people x  $3 \times 10^9$  bases/person). So far, only  $2 \times 10^{-10}$  percent of all human genetic information is known.

10 The rate of sequencing of the human genome by all world-wide efforts is roughly  $3 \times 10^9/15$  years, or 550,000 bases/day, at a cost of  $>\$1/\text{base}$ . Sequencing by the methods of the invention described herein will constitute an inordinate breakthrough in the rate of sequencing. The predicted time to complete one human genome with one machine is  $\sim 15$  hours. Several dynamic arrays in parallel will be able to complete the sequence of one human  
15 genome in a fraction of an hour.

A method for sequencing a polymer of linked units is also encompassed by the invention. The method is performed by obtaining polymer dependent impulses from each of a plurality of overlapping polymers, at least a portion of each of the polymers having a sequence of linked units identical to the other of the polymers, and comparing the polymer  
20 dependent impulses to obtain a sequence of linked units which is identical in the plurality of polymers.

The plurality of overlapping polymers is a set of polymers in which each polymer has at least a portion of its sequence of linked units which is identical to the other polymers. The portion of sequence which is identical is referred to as the overlapping region and which  
25 includes at least ten contiguous units.

A "polymer" as used herein is a compound having a linear backbone of individual units which are linked together by linkages. In some cases the backbone of the polymer may be branched. Preferably the backbone is unbranched. The term "backbone" is given its usual meaning in the field of polymer chemistry. The polymers may be heterogeneous in backbone  
30 composition thereby containing any possible combination of polymer units linked together such as peptide- nucleic acids (which have amino acids linked to nucleic acids and have enhanced stability). In a preferred embodiment the polymers are homogeneous in backbone

composition and are, for example, nucleic acids, polypeptides, polysaccharides, carbohydrates, polyurethanes, polycarbonates, polyureas, polyethyleneimines, polyarylene sulfides, polysiloxanes, polyimides, polyacetates, polyamides, polyesters, or polythioesters. In the most preferred embodiments, the polymer is a nucleic acid or a polypeptide. A

5 “nucleic acid” as used herein is a biopolymer comprised of nucleotides, such as deoxyribose nucleic acid (DNA) or ribose nucleic acid (RNA). A polypeptide as used herein is a biopolymer comprised of linked amino acids.

As used herein with respect to linked units of a polymer, “linked” or “linkage” means two entities are bound to one another by any physicochemical means. Any linkage known to  
10 those of ordinary skill in the art, covalent or non-covalent, is embraced. Such linkages are well known to those of ordinary skill in the art. Natural linkages, which are those ordinarily found in nature connecting the individual units of a particular polymer, are most common. Natural linkages include, for instance, amide, ester and thioester linkages. The individual units of a polymer analyzed by the methods of the invention may be linked, however, by  
15 synthetic or modified linkages. Polymers where the units are linked by covalent bonds will be most common but also include hydrogen bonded, etc..

The polymer is made up of a plurality of individual units. An “individual unit” as used herein is a building block or monomer which can be linked directly or indirectly to other building blocks or monomers to form a polymer. The polymer preferably is a polymer of at  
20 least two different linked units. The at least two different linked units may produce or be labeled to produce different signals, as discussed in greater detail below. The particular type of unit will depend on the type of polymer. For instance DNA is a biopolymer composed of a deoxyribose phosphate backbone composed of units of purines and pyrimidines such as adenine, cytosine, guanine, thymine, 5-methylcytosine, 2-aminopurine,  
25 2-amino-6-chloropurine, 2,6-diaminopurine, hypoxanthine, and other naturally and non-naturally occurring nucleobases, substituted and unsubstituted aromatic moieties. RNA is a biopolymer comprised of a ribose phosphate backbone composed of units of purines and pyrimidines such as those described for DNA but wherein uracil is substituted for thymidine. The DNA nucleotides may be linked to one another by their 5’ or 3’ hydroxyl group thereby  
30 forming an ester linkage. The RNA nucleotides may be linked to one another by their 5’, 3’ or 2’ hydroxyl group thereby forming an ester linkage. Alternatively, DNA or RNA units

having a terminal 5', 3' or 2' amino group may be linked to the other units of the polymer by the amino group thereby forming an amide linkage.

Whenever a nucleic acid is represented by a sequence of letters it will be understood that the nucleotides are in 5' → 3' order from left to right and that "A" denotes adenosine, "C" denotes cytidine, "G" denotes guanosine, "T" denotes thymidine, and "U" denotes uracil unless otherwise noted.

The polymers may be native or naturally-occurring polymers which occur in nature or non-naturally occurring polymers which do not exist in nature. The polymers typically include at least a portion of a naturally occurring polymer. The polymers can be isolated or synthesized *de novo*. For example, the polymers can be isolated from natural sources e.g. purified, as by cleavage and gel separation or may be synthesized e.g., (i) amplified *in vitro* by, for example, polymerase chain reaction (PCR); (ii) synthesized by, for example, chemical synthesis; (iii) recombinantly produced by cloning, etc.

The polymer or at least one unit specific marker thereof is in a form which is capable of interacting with an agent or station to produce a signal (polymer dependent impulse) characteristic of that interaction. The unit specific marker of a polymer which is capable of undergoing such an interaction is said to be labeled. If a unit specific marker of a polymer can undergo that interaction to produce a characteristic signal, then the polymer is said to be intrinsically labeled. It is not necessary that an extrinsic label be added to the polymer. If a non-native molecule, however, must be attached to the individual unit specific marker of the polymer to generate the interaction producing the characteristic signal, then the polymer is said to be extrinsically labeled. The "label" may be, for example, light emitting, energy accepting, fluorescent, radioactive, or quenching.

Many naturally occurring units of a polymer are light emitting compounds or quenchers. For instance, nucleotides of native nucleic acid molecules have distinct absorption spectra, e.g., A, G, T, C, and U have absorption maximums at 259 nm, 252 nm, 267 nm, 271 nm, and 258 nm respectively. Modified units which include intrinsic labels may also be incorporated into polymers. A nucleic acid molecule may include, for example, any of the following modified nucleotide units which have the characteristic energy emission patterns of a light emitting compound or a quenching compound: 2,4-dithiouracil, 2,4-Diselenouracil, hypoxanthine, mercaptopurine, 2-aminopurine, and selenopurine.

A unit or unit specific marker may also be considered to be intrinsically labeled when a property of the unit specific marker other than a light emitting, quenching or radioactive property provides information about the identity of the unit specific marker without the addition of an extrinsic label. For instance the shape and charge of the unit specific marker provides information about the unit specific marker which can result in a specific characteristic signal, such as a change in conductance arising from the blockage of a conductance path by the unit.

The types of labels useful according to the methods of the invention, guidelines for selecting the appropriate labels, and methods for adding extrinsic labels to polymers are provided in more detail in co-pending PCT patent application PCT/US98/03024 and US Serial No. 09/134,411, which are incorporated by reference.

In addition to information about a specific unit the methods of the invention may be used to identify greater than one unit at a time in order to provide information about a polymer. As discussed herein the invention is useful for detecting polymer dependent impulses arising from unit specific markers, which encompass single units as well as multiple units. In one aspect the method is carried out by providing a labeled polymer of linked units, detecting signals from labeled unit specific markers of less than all of the linked units, and storing a signature of the signals detected to analyze the polymer. In this aspect of the invention each unit of the labeled polymer may be labeled with a unit specific marker or less than all of the units may be labeled with a unit specific marker.

This method is particularly useful for analyzing multiple units of a polymer at one time. This is accomplished by using a unit specific marker which is labeled and which interacts with more than one unit in a sequence specific manner. As used herein a "unit specific marker" is a compound which specifically interacts with one or more units of a polymer and is capable of identifying those units. For instance a unit specific marker for a nucleic acid molecule can be a labeled dimers, trimers, etc. which bind to a specific sequence of bases, such as TG, AG, ATC, etc. By identifying the presence or position of the labeled markers structural information about the polymer can be derived. For instance, the presence of the marker on a polymer can reveal the identity of the polymer. This enables the presence or absence of a polymer in a solution or mixture of polymers to be determined. The order, distance, number etc. of the markers on a polymer can provide information about the sequence or composition of a polymer. Other unit specific markers include but are not limited



to sequence specific major and minor groove binders and intercallators, sequence specific DNA and peptide binding proteins, sequence specific peptide-nucleic acids, mass labels, fluorophores, antibodies or fragments thereof, restriction enzymes, probes, doubly tagged nucleotides, etc. Many such unit specific markers exist and are well known to those of skill in the art.

A "labeled unit specific marker" as used herein is any unit specific marker in a polymer that identifies a particular unit or units. A labeled unit specific marker includes, for instance, fluorescent markers which are bound to a particular unit or units, proteins, peptides, nucleic acids, polysaccharides, short oligomers, tRNA, etc. that recognize and bind to a particular unit or units and that can be detected by e.g., possessing an intrinsically labeled property or including an extrinsic label or by binding to another detection molecule such as an antibody.

This type of analysis can be used in one embodiment to identify DNA fragments by analyzing the hybridization patterns of multiple probes to individual fragments of polymers. The current state-of-the-art methods for hybridization analysis of DNA rely upon DNA chips. The methods of the invention are advantageous for a number of reasons. The number, type, order, and distance between the multiple probes bound to an unknown fragment of DNA can be determined. This information can be used to identify the number of differentially expressed genes unambiguously. Current hybridization approaches can only determine the type of probes bound to a given fragment. Furthermore, the methods of the invention are able to quantitate precisely the actual number of particular expressed genes. Current methods rely on quantitation of fluorescence intensities, which often give rise to errors due to non-linearities in the detection system. Given the great amount of information generated, the methods of the invention do not require a selection of expressed genes or unknown nucleic acids to be assayed. This is in contrast to the requirement of different DNA chips for different genes, sets of expressed genes to be analyzed, and also different organisms. The methods of the invention can identify the unknown expressed genes by computer analysis of the hybridization patterns generated. The data obtained from linear analysis of the DNA probes are then matched with information in a database to determine the identity of the target DNA. The methods can thus analyze information from hybridization reactions, which can then be applied to diagnostics and determination of gene expression patterns.

A "signature" as used herein is a sequence-specific signal arising from a labeled polymer. The signature includes information about the structure of the polymer. For instance, the signature of a polymer may be defined by a series of consecutive unit specific markers or by specific unit specific markers spaced a particular distance apart from one another. The signature of the polymer identifies the polymer. Signatures are useful for uniquely identifying fragments by identifying bases at certain positions along the length of a strand of DNA. The probability of knowing any one position is  $1/4$ . Unambiguous identification of a fragment comes with roughly twenty positions identified ( $(1/4)^{20} = 9.1 \times 10^{-13}$ ). For a fragment with 20 detected labels and 10% detection/labeling, the size of the fragment needs to be only 200 base pairs. The proposed read length is on the order of kilobases, which should unambiguously identify any fragment. The identification of fragments allows for grouping by similar sequences, making sequence reconstruction by population analysis possible.

The data obtained from the polymer dependent impulses may be stored in a database, or in a data file, in the memory system of the computer. The data for each polymer may be stored in the memory system so that it is accessible by the processor independently of the data for other polymers, for example by assigning a unique identifier to each polymer.

The information contained in the data and how it is analyzed depends on the number and type of labeled unit specific markers that were caused to interact with the agent to generate signals. For instance if every unit specific marker of a single polymer, each type of unit specific marker (e.g., all the A's of a nucleic acid) having a specific type of label, is labeled then it will be possible to determine from analysis of a single polymer the order of every unit specific marker within the polymer. If, however, only one of the four types of units of a nucleic acid is labeled then more data will be required to determine the complete sequence of the nucleic acid. Additionally, the method of data analysis will vary depending on whether the polymer is single stranded or double stranded or otherwise complexed. Several labeling schemes and methods for analysis using the computer system data produced by those schemes are described in more detail below. The labeling strategies are described with respect to nucleic acids for ease of discussion. Each of these strategies, however, is useful for labeling all polymers.

Several different strategies of labeling are possible, involving permutations of different types of units labeled, different percentage of units labeled, and single-stranded or

double-stranded labeling. Set forth below are examples of labeling strategies useful according to the invention. The invention is, however, not limited to the exemplary details provided below. The labeling methods described herein and data obtained from such methods are described with reference to DNA to simplify the discussion. The invention, however, is not limited to methods of analyzing DNA, but rather may be utilized with any type of polymer which is composed of individual monomeric units. It will be clear to those of ordinary skill in the art that when the description below refers to DNA or nucleic acids, any polymer may be substituted, and when the description refers to a nucleotide, a base or specifically A, C, T, or G, these terms may be substituted with the particular monomeric units of the desired polymer. For instance, the polymer may be a peptide, and in that case the monomeric units is an amino acid. The simplest labeling scheme involves the labeling of all four nucleotides with different labels. Labeling schemes in which three, two, or even one unit are labeled, or wherein various combinations of units are labeled using unit specific markers which span multiple nucleotides also possible.

A four nucleotide labeling scheme can be created where the A's, C's, G's, and T's of a target DNA is labeled with different labels. Such a molecule, if moved linearly past a station, will generate a linear order of signals which correspond to the linear sequence of nucleotides on the target DNA. The advantage of using a four nucleotide strategy is its ease of data interpretation and the fact that the entire sequence of unit specific markers can be determined from a single labeled polymer. Adding extrinsic labels to all four bases, however, may cause steric hindrance problems. In order to reduce this problem the intrinsic properties of some or all of the nucleotides may be used to label the nucleotides. As discussed above, nucleotides are intrinsically labeled because each of the purines and pyrimidines have distinct absorption spectra properties. In each of the labeling schemes described herein the nucleotides may be either extrinsically or intrinsically labeled but it is preferred that at least some of the nucleotides are intrinsically labeled when the four nucleotide labeling method is used. It is also preferred that when extrinsic labels are used with the four nucleotide labeling scheme that the labels be small and neutral in charge to reduce steric hindrance.

A three nucleotide labeling scheme in which three of the four nucleotides are labeled may also be performed. When only three of the four nucleotides are labeled analysis of the data generated by the methods of the invention is more complicated than when all four nucleotides are labeled. The data is more complicated because the number and position of the

nucleotides of the fourth unlabeled type must be determined separately. One method for determining the number and position of the fourth nucleotide utilizes analysis of two different sets of labeled nucleic acid molecules. For instance, one nucleic acid molecule may be labeled with A, C, and G, and another with C, G, and T. Analysis of the linear order of labeled nucleotides from the two sets yields sequence data. The three nucleotides chosen for each set can have many different possibilities as long as the two sets contain all four labeled nucleotides. For example, the set ACG can be paired with a set of labeled CGT, ACT or AGT.

The sequence including the fourth nucleotide also may be determined by using only a single labeled polymer rather than a set of at least two differently labeled polymers using a negative labeling strategy to identify the position of the fourth nucleotide on the polymer. Negative labeling involves the identification of sequence information based on units which are not labeled. For instance, when three of the nucleotides of a nucleic acid molecule are labeled with a label which provides a single type of signal, the points along the polymer backbone which are not labeled must be due to the fourth nucleotide. This can be accomplished by determining the distance between labeled nucleotides on a nucleic acid molecule. For example A, C, and G are labeled and the detectable signals generated indicated that the nucleic acid molecule had a sequence of AGGCAAACG (SEQ. ID. No. 1). If the distances between each of the nucleotides in the nucleic acid molecule are equivalent to the known inter-nucleotide distance for a particular combination of nucleotides except the distance between G and G is twice the normal inter-nucleotide distance then a T is positioned between the two G's and the entire molecule has a sequence of AGTGCAAACG (SEQ. ID. No. 2). The distance between nucleotides can be determined in several ways. Firstly, the polymer and the station may be moved relative to one another in a linear manner and at a constant rate of speed such that a single unit specific marker of the nucleic acid molecule will pass the station at a single time interval. If two time intervals elapse between detectable signals then the unlabeled nucleotide which is not capable of producing a detectable signal is present within that position. This method of determining the distance between unit specific markers is discussed in more detail below in reference to random one base labeling. Alternatively the polymer and the station may be caused to interact with one another such that each unit specific marker interacts simultaneously with a station to produce simultaneous detectable signals. Each detectable signal generated occurs at the point along the polymer

where the unit specific marker is positioned. The distance between the detectable signals can be calculated directly to determine whether an unlabeled unit specific marker is positioned anywhere along the nucleic acid molecule.

Nucleic acid molecules may also be labeled according to a two nucleotide labeling scheme. Six sets of two nucleotide labeled nucleic acid molecule can be used to resolve the data and interpret the nucleotide sequence. Ambrose et al., 1993 and Harding and Keller, 1992 have demonstrated the synthesis of large fluorescent DNA molecules with two of the nucleotides completely extrinsically labeled. The average size of the molecules were 7 kb. Six different combinations of two nucleotide labeling are possible using the following formula:

$$({}_nC_k) = \frac{n!}{k!(n-k)!} = \frac{4!}{2!2!} = 6$$

where n nucleotides are taken k at a time. The possible combinations are AC, AG, AT, CG, CT, and GT. Knowledge of the linear order of the labels in each of the sets allows for successful reconstruction of the nucleic acid sequence. Using a 4-mer (5'ACGT'3) as a model sequence, the theory can be demonstrated. The first set, AC, gives the information that there must be a C after the A. This does not give information about the number of nucleotides intervening the A and the C nor does it give information about any G's or T's preceding the A. The second set, AG, shows that there is also a G after the A. Set AT shows there is a T after the A. From these three sets, it is then known that the target DNA is a 4-mer and that one C, one G, and one T follow the A. The subsequent sets give information on the ordering of these three nucleotides following the A. Set CG shows that G follows C. Set CT shows that T follows C. Set GT finishes the arrangement to give the final deciphered sequence of 5'ACGT'3. In addition to the method using six labeled sets of nucleic acid molecules, the sequence can be established by combining information about the distance between labeled nucleotides generating detectable signals as described above and information obtained from fewer than six sets of two nucleotide labeled nucleic acid molecules.

A fourth labeling scheme, the random one nucleotide labeling scheme also may be used. In this method, distance information which is obtained by either population analysis and/or instantaneous rate of DNA movement is used to determine the number of nucleotides separating two labeled nucleotides. Analysis of four differently labeled target molecules yields the complete sequence.

One method of analysis with these labeling methods includes the use of complementary base information. Figure 1 demonstrates the labeling strategy in which two differently labeled DNA samples are required. The first sample has two of its non-complementary bases randomly labeled with the same fluorophore. Non-complementary pairs of bases are AC, AG, TC, and TG. The second sample has one of its bases randomly labeled. The base chosen for the second sample can be any of the four bases. In the example given, the two non-complementary bases are chosen to be A and C. As a result, two samples are prepared, one with labeled A's and C's and another with labeled A's. The DNA can be, for example, genomically digested, end-labeled, purified, and analyzed by nanochannel FRET sequencing. The sequence-specific FRET information arising from each fragment is sorted into one of two complementary strand groups. Sorting allows population analysis to determine the positions of all the desired bases. The figure illustrates the generation of sequence information from the sorted data. The first group of analyzed information yields the positions of all the A's and C's on one strand. The second group analyzed yields knowledge of all the A's and C's on one strand. The same procedure is applied to the complementary stand. Knowledge of the complementary strand's A's and C's is identical to knowledge of the T's and G's on the other stand. The result is sequence reconstruction. To cross-verify the sequence, the process can be repeated for the other pairs of non-complementary bases such as TG, TC and AG.

There are two methods of determining the distance between bases. One requires determining the instantaneous rate of DNA movement, which is readily calculated from the duration of energy transfer or quenching for a particular label. Another involves analyzing a population of target DNA molecules and its corresponding Gaussian distance distributions.

The instantaneous rate method, involves a determination of distance separation based on the known instantaneous rate of DNA movement ( $v$ ) multiplied by the time of separation between signals ( $t$ ). Instantaneous rate is found by measuring the time that it takes for a labeled nucleotide to pass by the interaction station. Since the length of the concentrated area of agent ( $d$ ) is known (through calibration and physical measurement of the localized region of the agent, e.g., the thickness of a concentrated donor fluorophore area), the rate is simply  $v=d/t$ . As shown in Figure 2 analysis of raw data demonstrating changes in energy emission patterns resulting from sequential detectable signals when plotted produces a curve which from left to right shows two energy intensity decreases, followed by two energy intensity

increases. The plateau from the first energy intensity decrease (denoted  $t_1$ ) is double that of the second plateau ( $t_2$ ). The length of the interaction station is given as 51 Å. From this given information, the number of labeled nucleotides is known. Furthermore, the distance of separation of the two is determined by relating the rate of DNA movement to the time of the donor intensity plateaus.

The number of labeled nucleotides is simply denoted by the number of intensity decreases. In Figure 2, there are two intensity decreases. Accordingly, there must be two detectable labels on the DNA. To determine the distance of base separation, it is necessary to know the instantaneous rate of DNA movement, which is found by knowing the time for one labeled nucleotide to cross the localized region of the agent and the length of the localized region of the agent. The length of the localized region of the agent is given as 51 Å. The time for one labeled nucleotides crossing the localized region of the agent is bounded by the first intensity decrease and the first intensity increase (denoted as the gray shaded region, 7.5 s). The rate of DNA movement is 6.8 Å/s. The base separation is derived from the time separating the labeled nucleotides ( $t_1 = 5$  s) multiplied by the rate (6.8 Å), which is equal to 10 base pairs. As a means of cross-verification,  $51 \text{ Å} - t_2v$  also yields the base separation.

In the population method the entire population of labeled nucleotide is considered. Knowledge of the length of the localized region of the agent and instantaneous rate, as required for the rate method, is not necessary. Use of population analyses statistically eliminates the need for precision measurements on individual nucleic acid molecules.

An example of population analyses using five nucleic acid molecules each traversing a nanochannel is described below. Five molecules representing a population of identical DNA fragments are prepared. In a constant electric field, the time of detection between the first and second labeled nucleotide should be identical for all the DNA molecules. Under experimental conditions, these times differ slightly, leading to a Gaussian distribution of times. The peak of the Gaussian distribution is characteristic of the distance of separation ( $d$ ) between two labeled nucleotides.

An additional example utilizing a population of one nucleotide randomly labeled nucleic acid molecule (six molecules represent the population) further illustrates the concept of population analysis and the determination of distance information. The nucleic acid is end-labeled to provide a reference point. With enough nucleic acid molecules, the distance between any two A's can be determined. Two molecules, when considered as a sub-

population, convey the base separation molecules, distributions of 4 and 6 base separations are created. Extending the same logic to rest of the population, the positions of all the A's on the DNA can be determined. The entire sequence is generated by repeating the process for the other three bases (C, G, and T).

5 In addition to labeling all of one type of unit specific marker in the above-described examples, it is possible to use various labeling schemes where not every nucleotide of the nucleotides or markers to be labeled is labeled. An outline of a one nucleotide labeling scheme where less than all of the one nucleotide are labeled is shown in Figure 3. A representative population of random A-labeled fragments for a 16-mer with the sequence  
10 5'ACGTACGTACGTACGT'3 (SEQ. ID. No. 3). Each individually labeled DNA molecule has half of its A's labeled in addition to 5' and 3' end labels. With a large population of randomly labeled fragments, the distance between every successive A on the target DNA can be found. The end labels serve to identify the distance between the ends of the DNA and the first A. Repeating the same analysis for the other nucleotides generates the sequence of the  
15 16-mer by compiling the data to identify the position of all of the As within that population of nucleic acid molecules. These steps can then be repeated using unit specific markers for the other nucleotides in the population of nucleic acids. The advantages of using such a method includes lack of steric effects and ease of labeling. This type of labeling is referred to as random labeling. A polymer which is "randomly labeled" is one in which fewer than all of a  
20 particular type of unit specific marker are labeled. It is unknown which unit specific markers of a particular type of a randomly labeled polymer are labeled.

A similar type of analysis may be performed by labeling each of the four nucleotides incompletely but simultaneously within a population. For instance, each of the four nucleotides may be partially labeled with its own unit specific marker which gives rise to a  
25 different physical characteristic, such as color, size, etc. This can be accomplished to generate a data set containing information about all of the nucleotides from a single population analysis. For instance the method may be accomplished by partially labeling two nucleotide pairs at one time. Two nucleotide labeling is possible through the lowering of steric hindrance effects by using unit specific markers which recognize the two nucleotides of  
30 a nucleic acid strand and which contain a label such as a single fluorescent molecule. Ambrose et al., 1993 and Harding and Keller, 1992 have demonstrated that large fluorescent nucleic acid molecules with two of the nucleotides completely labeled are possible to achieve.



The average size of the molecules studied were 7KB. Figure 4 demonstrates a two nucleotide labeling scheme. Partial labeling of three nucleotides is also possible. For instance, each of three nucleotides is partially labeled with a different unit specific marker. In this case, a population of single stranded nucleic acid molecules which are partially labeled with three specific nucleotide pair combinations is generated and can be analyzed.

The methods of the invention can also be achieved using a double stranded nucleic acid. In a double stranded nucleic acid, when a single nucleotide on two of the strands is labeled, information about two nucleotides becomes available for each of the strands. For instance, in the random and partial labeling of A's, knowledge about the A's and T's becomes available. Figure 5 demonstrates a labeling strategy in which two differently labeled nucleic acid samples are prepared. The first sample has two non-complimentary nucleotides randomly labeled with the same fluorophore. Non-complimentary pairs of nucleotides are AC, AG, TC, and TG. The second sample has one of its nucleotides randomly labeled. The nucleotide chosen for the second sample may be any one of the four nucleotides. In the example provided, the two non-complimentary nucleotides are chosen to be A and C, and the single nucleotide is chosen to be A. Two samples are prepared, one with labeled A's and C's and another with labeled A's. The nucleic acid is genomically digested, end labeled, purified, and analyzed. Such procedures are well-known to those of ordinary skill in the art. The information from each fragment is sorted into one of two complimentary strand groups. Sorting the information allows the population analysis to determine the positions of all the desired nucleotides. Figure 6 illustrates the generation of sequence information from the sorted data. The first group of data provides known positions of all the A's and C's on one strand. The second group of data provides known positions of all of the A's. The combination of these two data sets reveals the position of all of the A's and C's on one strand. The same procedure may be applied to the complimentary strand to determine the positions of the A's and C's on that strand. The resultant data reveals the entire sequence for both strands of the nucleic acid, based on the assumption that the strand includes the complimentary nucleotide pairs of A and C (A:T and C:G). To cross-verify the sequence, the process can be repeated for the other pairs of non-complimentary nucleotides such as TG, TC and AG.

A single-stranded two-nucleotide labeling scheme also can be performed on double stranded DNA when two of the nucleotides on one strand of DNA are fully replaced by labeled nucleotides. To reduce the steric constraints imposed by two extrinsically labeled

nucleotides while preserving the theory behind two-nucleotide labeling, it is possible to label one nucleotide fully on each of the complementary strands to achieve the same end. This method involves using double-stranded DNA in which each strand is labeled with a different label. Six differently labeled duplex DNA sets will produce a data set which is adequate to provide sequence information. Each complementary strand of DNA should have one of the nucleotides labeled. In each of the duplex DNA sets, the equivalent of two different nucleotides (possible combinations are AC, AG, AT, CG, CT, GT) are labeled. When both complementary strands have the adenines labeled, this is equivalent to the combination AT. In duplex two-nucleotide labeling, the advantage is that only one nucleotide on each strand is labeled, allowing longer labeled strands to be synthesized as compared to two-nucleotide labeling on single-stranded DNA. In practice, it has been shown that synthesis of DNA fragments with one nucleotide completely labeled can be achieved with lengths much greater than 10 kb (Ambrose et al., 1993; Harding and Keller, 1992).

By including more than one physical characteristic into the label, the simultaneous and overlapping reading of the nucleic acid within the same temporal frame may provide more accurate and rapid information about the positions of the labeled nucleotides than when only a single physical characteristic is included. label with different wavelength fluorophores. For instance, as demonstrated in Figure 7, each of the nucleotides can include a double or triple Each of the fluorophores can be detected separately to provide distinct readings form the same sample.

In addition to the various combinations of single nucleotide labeling methods, two or more adjacent nucleotides may be specifically labeled. As described above a unit specific marker includes markers which are specific for individual nucleotides as well as markers which are specific for multiple nucleotides. Multiple nucleotides include two or more nucleotides which may or may not be adjacent. For instance if a unit specific marker is a complex of protein, the complex of proteins may interact with specific nucleotides that are adjacent to one another or which are separated by random nucleotides. This type of analysis is particularly useful because detection of the signal requires less resolution than with single nucleotide analysis. The more complex the analysis, the greater resolution of the system. Resolution as used herein refers to the number of nucleotides which can be resolved by the appropriate signal detection method used.

The signal detection method is described in more detail below. Preferably it includes methods such as nanochannel analysis, near-field scanning microscopy, atomic force microscopy, scanning electron microscopy, waveguide structures, etc.

The greater the number of nucleotides a unit specific marker spans and recognizes, the more amenable that unit specific marker is to low resolution means of detection. For any given number of nucleotide-spanning markers, the number of different unit specific markers which can be used is defined by the formula  $4^n$ , where  $n$  is the number of nucleotides detected by the unit specific marker. A unit specific marker which spans two nucleotides would be specific for one of 16 combinations of nucleotide pairs. These include, AC, AG, AT, AA, CC, CA, CG, CT, GA, GG, GC, GT, TA, TC, TG, and TT. A unit specific marker which spans three nucleotides would be specific for one of a combination of 64 three nucleotide pairs combinations. More than three nucleotide pairs combinations may also be used, and the number would increase according to the above formula. Using these types of unit specific markers, nucleotide sequence information can be reconstructed through a number of different means. The information generated from the reconstruction of the unit specific markers is not limited to the generation of sequence information, but additionally can be used to unambiguously identify fragments, provide the specific number of that combination of nucleotides found within the sequence, etc.

Various combinations of triplet unit specific markers bound to a nucleic acid molecule can be deciphered and analyzed using these methods. Without knowing the precise location of the triplet unit specific markers on the nucleic acid, the specificity given to a bound nucleic acid fragment is given as  $N/4^n$  where  $N$  is the number of nucleotides in the fragment of target nucleic acid and  $n$  is the number of bound sites on the nucleic acid. The longer the strand of nucleic acid, the lower the specificity of the particular system. The specificity of the bound unit specific markers can be increased by determining the precise location of the triplet unit specific markers. In this case, the specificity is increased to  $1/4^n$  which is the same as if an  $N$ -mer were bound to the target strand of nucleic acid.

The simplest method to determine the sequence of the nucleic acid molecule from the set of triplet unit specific markers is to examine two triplet unit specific markers one time until all 64 unit specific markers are examined. If one of the triplet unit specific markers is kept constant during the analysis, the analysis is simplified. An example of this type of analysis is presented in Figure 8. In the example, a short stretch of nucleic acid is analyzed

using two triplet unit specific markers. The triplet unit specific markers are CGX and GXX. Using these markers, the two based positions after the first ACG triplet can be determined. Using the 63 different triplets together with the initial fragment ACG, information about flanking nucleotides and the contiguous sequence of the intervening nucleotides between the ACGs can be determined.

Using these methods of sequence analysis, problems which occur in other types of hybridization, etc. analysis are avoided. For instance, repeated sequences such as the Alu repeats in the human genome create analysis problems using hybridization sequencing methods. Such problems are avoided using the methods described herein. Using the methods described herein the number of repeats can be simply counted by the different triplets bound in each of the states. Hybridization sequencing analysis does not allow the determination of linear order or number of probes found between two probe sequences. The linear order and the precise quantitation of the number of probes bound allows an additional order of information which bypasses the difficulties faced in sequencing by hybridization. The methods of the invention are thus rapid and straightforward.

The method using triplet, etc. unit specific markers does not need to be performed sequentially. For instance, several triplets may be assayed simultaneously to provide an even more rapid method of analysis. The only limitation in simultaneous analysis is that none of the triplet unit specific markers used simultaneously should overlap one another. Therefore, the choice of one particular triplet sequence precludes the simultaneous use of triplet sequences which would overlap with that sequence. For example if the triplet sequence ACG is selected for analysis, 4 of the 64 sets of triplets may not be used during simultaneous analysis with this triplet. These include XXA, XAC, GXX, and CGX. Mathematically, the maximum number of fragments which a triplet label can preclude simultaneous probing with is determined by the following equation:

$$2[\sum 4^2 + 4^1] \text{ or generally } 2[\sum 4^{n-1} + 4^{n-2} \dots 4^1]$$

where n is the number of nucleotides spanned by the labels. The sum is that a maximum of 40 fragments are precluded from simultaneous assay with the originally selected ACG triplet. Therefore, a total of 24 different fragments may be assayed at one time.

Double stranded nucleic acid analysis also may be accomplished using direction specific labels such as those shown in Figure 9. Direction specific labels allow for discrimination between a combination of nucleotides such as ACG triplet on either strand. In

the case of direction specific labels, the reversal of the center bound label shows that it is a label bound on the opposite strand. The labels have 5' to 3' or 3' to 5' directionality.

One use for the methods of the invention is to determine the sequence of units within a polymer. Identifying the sequence of units of a polymer, such as a nucleic acid, is an important step in understanding the function of the polymer and determining the role of the polymer in a physiological environment such as a cell or tissue. The sequencing methods currently in use are slow and cumbersome. The methods of the invention are much quicker and generate significantly more sequence data in a very short period of time.

The analysis methods described herein may be linear or non linear. The methods for generating sequence information based on data obtained from partially labeled polymers can be applied to data obtained by any method that produces polymer dependent impulses. The reconstruction of the sequence of the polymer from this type of data is an integral aspect of the invention. As long as the data is obtained by a method for detecting the polymer dependent impulses, whether it is obtained in a linear manner or not, the data may be analyzed according to the methods of the invention.

The signals may be detected sequentially or simultaneously. As used herein signals are detected "sequentially" when signals from different unit specific markers of a single polymer are detected spaced apart in time. Not all unit specific markers need to be detected or need to generate a signal to detect signals "sequentially." When the unit specific markers are sequentially exposed to the station the unit specific marker and the station move relative to one another. As used herein the phrase "the unit specific marker and the station move relative to one another" means that either the unit specific marker and the station are both moving or only one of the two is moving and the other remains stationary at least during the period of time of the interaction between the unit specific marker and the station. The unit specific marker and the station may be moved relative to one another by any mechanism. For instance the station may remain stationary and the polymer may be drawn past the station by an electric current. Other methods for moving the polymer include but are not limited to movement resulting from a magnetic field, a mechanical force, a flowing liquid medium, a pressure system, a gravitational force, and a molecular motor such as e.g., a DNA polymerase or a helicase when the polymer is DNA or e.g., myosin when the polymer is a peptide such as actin. The movement of the polymer may be assisted by the use of a channel, groove or ring to guide the polymer. Alternatively the station may be moved and the polymer may remain

stationary. For instance the station may be held within a scanning tip that is guided along the length of the polymer.

In another embodiment signals are detected simultaneously. As used herein signals are "detected simultaneously" by causing a plurality of the labeled unit specific markers of a polymer to be exposed to a station at once. The plurality of the unit specific markers can be exposed to a station at one time by using multiple interaction sites. Signals can be detected at each of these sites simultaneously. For instance multiple stations may be localized at specific locations in space which correspond to the unit specific markers of the polymer. When the polymer is brought within interactive proximity of the multiple stations signals will be generated simultaneously. This may be embodied, for example, in a linear array of stations positioned at substantially equivalent distances which are equal to the distance between the unit specific markers. The polymer may be positioned with respect to the station such that each unit specific marker is in interactive proximity to a station to produce simultaneous signals.

Multiple polymers can be analyzed simultaneously by causing more than one polymer to move relative to respective stations at one time. The polymers may be similar or distinct. If the polymers are similar, the same or different unit specific markers may be detected simultaneously.

A preferred method for moving a polymer past a station according to the invention utilizes an electric field. An electric field can be used to pull a polymer through a channel because the polymer becomes stretched and aligned in the direction of the applied field as has previously been demonstrated in several studies (Bustamante, 1991; Gurrieri et al., 1990; Matsumoto et al., 1981).

Another method for moving a polymer past a station involves the use of a molecular motor. A molecular motor is a device which physically interacts with the polymer and pulls the polymer past the station. Molecular motors include but are not limited to DNA and RNA polymerases and helicases. DNA polymerases have been demonstrated to function as efficient molecular motors. Preferably the internal diameters of the regions of the polymerase which clamp onto the DNA is similar to that of double stranded DNA. Furthermore, large amounts of DNA can be able to be threaded through the clamp in a linear fashion. Molecular motors are described in more detail in co-pending US provisional patent application

60/096,540, filed August 13, 1998 and the US patent application claiming priority thereto, the entire contents of which is hereby incorporated by reference.

The overall structure of the  $\beta$ -subunit of DNA polymerase III holoenzyme is 80 Å in diameter with an internal diameter of ~35 Å. In comparison, a full turn of duplex B-form DNA is ~34 Å. The beta subunit fits around the DNA, in a mechanism referred to as a sliding clamp mechanism, to mediate the processive motion of the holoenzyme during DNA replication. It is well understood that the  $\beta$ -subunit encircles DNA during replication to confer processivity to the holoenzyme (Bloom et al., 1996; Fu et al., 1996; Griep, 1995; Herendeen and Kelly, 1996; Naktinis et al., 1996; Paz-Elizur et al., 1996; Skalter et al., 1996). Because the sliding clamp is the mechanism of processivity for a polymerase, it necessarily means that large amounts of DNA are threaded through the clamp in a linear fashion. Several kilobases are threaded through the clamp at one time (Kornberg and Baker, 1991).

The detectable signal (polymer dependent impulse) is produced at a station. A “station” as used herein is a region where a portion of the polymer to be detected, e.g. the unit specific marker, is exposed to, in order to produce a signal or polymer dependent impulse. The station may be composed of any material including a gas. Preferably the station is a non-liquid material. “Non-liquid” has its ordinary meaning in the art. A liquid is a non-solid, non-gaseous material characterized by free movement of its constituent molecules among themselves but without the tendency to separate. In another preferred embodiment the station is a solid material. In one embodiment when the interaction between the unit specific marker and the station produces a polymer dependent impulse the station is a signal generation station. One type of signal generation station is an interaction station. As used herein an “interaction station or site” is a region where a unit specific marker of the polymer interacts with an agent and is positioned with respect to the agent in close enough proximity whereby they can interact. The interaction station for fluorophores, for example, is that region where they are close enough so that they energetically interact to produce a signal.

The interaction station in one embodiment is a region of a nanochannel where a localized agent, such as an acceptor fluorophore, attached to the wall forming the channel, can interact with a polymer passing through the channel. The point where the polymer passes the localized region of agent is the interaction station. As each labeled unit specific marker of the polymer passes by the agent a detectable signal is generated. The agent may be localized

within the region of the channel in a variety of ways. For instance the agent may be embedded in the material that forms the wall of the channel or the agent may be attached to the surface of the wall material. Alternatively the agent may be a light source which is positioned a distance from the channel but which is capable of transporting light directly to a region of the channel through a waveguide. An apparatus may also be used in which multiple polymers are transported through multiple channels. These and other related embodiments of the invention are discussed in more detail below. The movement of the polymer may be assisted by the use of a groove or ring to guide the polymer.

Other arrangements for creating interaction stations are embraced by the invention.

For example, a polymer can be passed through a molecular motor tethered to the surface of a wall or embedded in a wall, thereby bringing unit specific markers of the polymer sequentially to a specific location, preferably in interactive proximity to a proximate agent, thereby defining an interaction station. A molecular motor is a biological compound such as polymerase, helicase, or actin which interacts with the polymer and is transported along the length of the polymer past each unit specific marker. Likewise, the polymer can be held from movement and a reader can be moved along the polymer, the reader having attached to it the agent. For instance the agent may be held within a scanning tip that is guided along the length of the polymer. Interaction stations then are created as the agent is moved into interactive proximity to each unit specific marker of the polymer.

The agent that interacts with the unit specific marker of the polymer at the interaction station is selected from the group consisting of electromagnetic radiation, a quenching source, and a fluorescence excitation source. "Electromagnetic radiation" as used herein is energy produced by electromagnetic waves. Electromagnetic radiation may be in the form of a direct light source or it may be emitted by a light emissive compound such as a donor fluorophore. "Light" as used herein includes electromagnetic energy of any wavelength including visible, infrared and ultraviolet.

As used herein, a quenching source is any entity which alters or is capable of altering a property of a light emitting source. The property which is altered can include intensity fluorescence lifetime, spectra, fluorescence, or phosphorescence.

A fluorescence excitation source as used herein is any entity capable of fluorescing or giving rise to photonic emissions (i.e. electromagnetic radiation, directed electric field, temperature, fluorescence, radiation, scintillation, physical contact, or mechanical disruption.)



For instance, when the unit specific marker is labeled with a radioactive compound the radioactive emission causes molecular excitation of an agent that is a scintillation layer which results in fluorescence.

When a unit specific marker of the polymer is exposed to the agent the interaction between the two produces a signal. The signal provides information about the polymer. For instance if all unit specific markers of a particular type, e.g., all of the alanines, of a protein polymer are labeled (intrinsic or extrinsic) with a particular light emissive compound then when a signal characteristic of that light emissive compound is detected upon interaction with the agent the signal signifies that an alanine residue is present at that particular location on the polymer. If each type of unit specific marker e.g., each type of amino acid is labeled with a different light emissive compound having a distinct light emissive pattern then each amino acid will interact with the agent to produce a distinct signal. By determining what each signal for each unit specific marker of the polymer is, the sequence of units can be determined.

The interaction between the unit specific marker and the agent can take a variety of forms, but does not require that the unit specific marker and the agent physically contact one another. Examples of interactions are as follows. A first type of interaction involves the agent being electromagnetic radiation and the unit specific marker of the polymer being a light emissive compound (either intrinsically or extrinsically labeled with a light emissive compound). When the light emissive unit specific marker is contacted with electromagnetic radiation (such as by a laser beam of a suitable wavelength or electromagnetic radiation emitted from a donor fluorophore), the electromagnetic radiation causes the light emissive compound to emit electromagnetic radiation of a specific wavelength. The signal is then measured. The signal exhibits a characteristic pattern of light emission and thus indicates that a particular labeled unit specific marker of the polymer is present. In this case the unit specific marker of the polymer is said to "detectably affect the emission of the electromagnetic radiation from the light emissive compound."

A second type of interaction involves the agent being a fluorescence excitation source and the unit specific marker of the polymer being a light emissive or a radioactive compound. When the light emissive unit specific marker is contacted with the fluorescence excitation source, the fluorescence excitation source causes the light emissive compound to emit electromagnetic radiation of a specific wavelength. When the radioactive unit specific

marker is contacted with the fluorescence excitation source, the nuclear radiation emitted from the unit specific marker causes the fluorescence excitation source to emit electromagnetic radiation of a specific wavelength. The signal then is measured.

5 A variation of these types of interaction involves the presence of a third element of the interaction, a proximate compound which is involved in generating the signal. For example, a unit specific marker may be labeled with a light emissive compound which is a donor fluorophore and a proximate compound can be an acceptor fluorophore. If the light emissive compound is placed in an excited state and brought proximate to the acceptor fluorophore, then energy transfer will occur between the donor and acceptor, generating a signal which can  
10 be detected as a measure of the presence of the unit specific marker which is light emissive. The light emissive compound can be placed in the "excited" state by exposing it to light (such as a laser beam) or by exposing it to a fluorescence excitation source.

Another interaction involves a proximate compound which is a quenching source. In this instance, the light emissive unit specific marker is caused to emit electromagnetic  
15 radiation by exposing it to light. If the light emissive compound is placed in proximity to a quenching source, then the signal from the light emissive unit specific marker will be altered.

A set of interactions parallel to those described above can be created wherein, however, the light emissive compound is the proximate compound and the unit specific marker is either a quenching source or an acceptor source. In these instances the agent is  
20 electromagnetic radiation emitted by the proximate compound, and the signal is generated, characteristic of the interaction between the unit specific marker and such radiation, by bringing the unit specific marker in interactive proximity with the proximate compound.

The mechanisms by which each of these interactions produces a detectable signal is known in the art. For exemplary purposes the mechanism by which a donor and acceptor  
25 fluorophore interact according to the invention to produce a detectable signal including practical limitations which are known to result from this type of interaction and methods of reducing or eliminating such limitations is set forth below.

Another preferred method of analysis of the invention involves the use of radioactively labeled polymers. The type of radioactive emission influences the type of  
30 detection device used. In general, there are three different types of nuclear emission including alpha, beta, and gamma radiation. Alpha emission cause extensive ionization in matter and permit individual counting by ionization chambers and proportional counters, but more

interestingly, alpha emission interacting with matter may also cause molecular excitation, which can result in fluorescence. The fluorescence is referred to as scintillation. Beta decay which is weaker than alpha decay can be amplified to generate an adequate signal. Gamma radiation arises from internal conversion of excitation energy. Scintillation counting of gamma rays is efficient and produces a strong signal. Sodium iodide crystals fluoresce with incident gamma radiation.

A "scintillation" layer or material as used herein is any type of material which fluoresces or emits light in response to excitation by nuclear radiation. Scintillation materials are well known in the art. Aromatic hydrocarbons which have resonance structures are excellent scintillator. Anthracene and stilbene fall into the category of such compounds. Inorganic crystals are also known to fluoresce. In order for these compounds to luminesce, the inorganic crystals must have small amounts of impurities, which create energy levels between valence and conduction bands. Excitation and de-excitation can therefore occur. In many cases, the de-excitation can occur through phosphorescent photon emission, leading to a long lifetime of detection. Some common scintillator include NaI (Tl), ZnS (Ag), anthracene, stilbene, and plastic phosphors.

Many methods of measuring nuclear radiation are known in the art and include devices such as cloud and bubble chamber devices, constant current ion chambers, pulse counters, gas counters (i.e., Geiger-Müller counters), solid state detectors (surface barrier detectors, lithium-drifted detectors, intrinsic germanium detectors), scintillation counters, Cerenkov detectors, etc.

Analysis of the radiolabeled polymers is identical to other means of generating polymer dependent impulses. For example, a sample with radiolabeled A's can be analyzed by the system to determine relative spacing of A's on a sample DNA. The time between detection of radiation signals is characteristic of the polymer analyzed. Analysis of four populations of labeled DNA (A's, C's, G's, T's) can yield the sequence of the polymer analyzed. The sequence of DNA can also be analyzed with a more complex scheme including analysis of a combination of dual labeled DNA and singly labeled DNA. Analysis of a and C labeled fragment followed by analysis of an A labeled version of the same fragment yields knowledge of the positions of the A's and C's. The sequence is known if the procedure is repeated for the complementary strand. The system can further be used for analysis of

polymer (polypeptide, RNA, carbohydrates, etc.), size, concentration, type, identity, presence, sequence and number.

The methods described above can be performed on a single polymer or on more than one polymer in order to determine structural information about the polymer.

5 In another preferred embodiment the signal generated by the interaction between the unit specific marker and the agent results from fluorescence resonance energy transfer (FRET) between fluorophores. Either the unit specific marker or the proximate compound/agent may be labeled with either the donor or acceptor fluorophore. FRET is the transfer of photonic energy between fluorophores. FRET has promise as a tool in  
10 characterizing molecular detail because of its ability to measure distances between two points separated by 10 Å to 100 Å. The angstrom resolution of FRET has been used in many studies of molecular dynamics and biophysical phenomena (for reviews see Clegg, 1995; Clegg, 1992; Selvin, 1995; and Wu and Brand, 1994). The resolving power of FRET arises because energy transfer between donor and acceptor fluorophores is dependent on the inverse sixth  
15 power of the distance between the probes. In practice, this resolution is about an order of magnitude better than that of the highest resolution electron microscope.

In order to undergo FRET, the emission spectrum of the donor overlaps with the excitation spectrum of the acceptor. The unit specific marker of the polymer is specifically labeled with an acceptor fluorophore. The agent is a donor fluorophore. A laser is tuned to  
20 the excitation wavelength of the donor fluorophore. As the polymer is moved through the channel, the donor fluorophore emits its characteristic wavelength. As the acceptor fluorophore moves into interactive proximity with the donor fluorophore, the acceptor fluorophore is excited by the energy from the donor fluorophore. The consequence of this interaction is that the emission of the donor fluorophore is quenched and that of the acceptor  
25 fluorophore is enhanced.

In order to generate an optimal efficient FRET signal for detection, two conditions should be satisfied. The first condition is efficient donor emission in the absence of acceptors. The second is efficient generation of a change in either donor or acceptor emissions during FRET. Each of these are described in more detail in co-pending PCT Patent  
30 Application PCT/US98/03024 and US Serial No. 09/134,411

A "detectable signal" as used herein is any type of signal or polymer dependent impulse which can be sensed by conventional technology. The signal produced depends on

the type of station as well as the unit specific marker and the proximate compound if present. In one embodiment the signal is electromagnetic radiation resulting from light emission by a labeled (intrinsic or extrinsic) unit specific marker of the polymer or by the proximate compound. In another embodiment the signal is fluorescence resulting from an interaction of a radioactive emission with a scintillation layer. The detected signals may be stored in a database for analysis. One method for analyzing the stored signals is by comparing the stored signals to a pattern of signals from another polymer to determine the relatedness of the two polymers. Another method for analysis of the detected signals is by comparing the detected signals to a known pattern of signals characteristic of a known polymer to determine the relatedness of the polymer being analyzed to the known polymer. Comparison of signals is discussed in more detail below.

More than one detectable signal may be detected. For instance a first individual unit specific marker may interact with the agent or station to produce a first detectable signal and a second individual unit specific marker may interact with the agent or station to produce a second detectable signal different from the first detectable signal. This enables more than one type of unit specific marker to be detected on a single polymer.

Once the signal is generated it can then be detected. The particular type of detection means will depend on the type of signal generated which of course will depend on the type of interaction which occurs between the unit specific marker and the agent. Many interactions involved in the method of the invention will produce an electromagnetic radiation signal. Many methods are known in the art for detecting electromagnetic radiation signals, including two- and three-dimensional imaging systems. These and other systems are described in more detail in co-pending PCT Patent Application PCT/US98/03024 and US Serial No. 09/134,411.

Other interactions involved in the method will produce a nuclear radiation signal. As a radiolabel on a polymer passes through the defined region of detection, such as the station, nuclear radiation is emitted, some of which will pass through the defined region of radiation detection. A detector of nuclear radiation is placed in proximity of the defined region of radiation detection to capture emitted radiation signals. Many methods of measuring nuclear radiation are known in the art including cloud and bubble chamber devices, constant current ion chambers, pulse counters, gas counters (i.e., Geiger-Müller counters), solid state detectors (surface barrier detectors, lithium-drifted detectors, intrinsic germanium detectors), scintillation counters, Cerenkov detectors, etc.

Other types of signals generated are well known in the art and have many detections means which are known to those of skill in the art. Among these include opposing electrodes, magnetic resonance, and piezoelectric scanning tips. Opposing nanoelectrodes can function by measurement of capacitance changes. Two opposing electrodes create an area of energy storage, which is effectively between the two electrodes. It is known that the capacitance of two opposing electrodes change when different materials are placed between the electrodes. This value is known as a dielectric constant. Changes in the dielectric constant can be measured as a change in the voltage across the two electrodes. In the present example, different nucleotide bases or unit specific markers of a polymer may give rise to different dielectric constants. The capacitance changes as the dielectric constant of the unit specific marker of the polymer per the equation:  $C=KC_0$ , where K is the dielectric constant and  $C_0$  is the capacitance in the absence of any bases. The voltage deflection of the nanoelectrodes is then outputted to a measuring device, recording changes in the signal with time.

A nanosized NMR detection device can be constructed to detect the passage of specific spin-labeled polymer unit specific markers. The nanosized NMR detection device consists of magnets which can be swept and a means of irradiating the polymer with electromagnetic energy of a constant frequency (This is identical to holding the magnetic field constant while the electromagnetic frequency is swept). When the magnetic field reaches the correct strength, the nuclei absorb energy and resonance occurs. This absorption causes a tiny electric current to flow in an antenna coil surrounding the sample. The signal is amplified and output to a recording device. For known labeled compounds, the time of detection is much faster than current means of NMR detection where a full spectra of the compound in question is required. Known labeled unit specific markers of polymers have known chemical shifts in particular regions, thereby eliminating the need to perform full spectral sweeps, lowering the time of detection per base to micro or milliseconds.

A nanoscale piezoelectric scanning tip can be used to read the different unit specific markers of the polymer based on physical contact of the different polymer unit specific markers with the tip. Depending on the size and shape of the polymer unit specific marker, different piezoelectric signals are generated, creating a series of unit specific marker dependent changes. Labels on unit specific markers are physically different than native units and can create a ready means for detection via a piezoelectric scanning tip. Upon contact of a

polymer unit specific marker with the tip, the piezoelectric crystals change and give rise to a current which is outputted to a detection device. The amplitude and duration of the current created by the interaction of the polymer unit specific marker and the tip is characteristic of the polymer unit specific marker.

5 In one preferred type of linear analysis, the labeled polymer is fixed in a relative position to a station by a nanochannel, such that as the labeled polymer passes the station signals arising from the interaction between the station and the labeled polymer are spacially confined. The channels preferably correspond to the diameter of the labeled polymer and fix the DNA relative to an imaging system which is able to capture many emissions from the  
10 labeled polymer over an integrated period of time. The method is specific for the analysis of intensities of individual molecules. The nanochannel system is provided as an example and is discussed in more detail below. Any means can be used to fix the labeled polymers in a dimension for analysis by an optical method capable of analyzing the signals over time. Examples of devices which are capable of positioning labeled polymers for analysis include  
15 nanochannel arrays, integrated nanofabricated waveguides, and various lattices.

The methods of the invention are described herewith reference to several examples using polymers which are fluorescently labeled and which are analyzed using a nanochannel device to simplify the discussion. The invention, however, is not limited to these examples and the other embodiments will be described more fully herein. In the example, fluorescently  
20 labeled polymers are drawn through a series of nanochannels. The planar surface of the nanochannels is illuminated via epiillumination. As the polymers cross the nanochannels, they are fixed in position relative to the imaging device, allowing for integration of the polymers fluorescence over time. The corresponding brightness of the fluorescence spots is indicative of the approximate length of the labeled polymers. The rationale behind the use of  
25 the restrictive structures is to fix the molecules relative to the detection system so that photon collection can occur in a fixed spatial dimension over time. In the embodiments when intensity is not being measured there is no need to fix the polymer relative to the imaging device. The time period that the polymer is fixed may be very short, and is just enough to make an intensity measurement.

30 As mentioned above, the signals arising from the polymers provide structural information about the polymer. The types of structural information that can be obtained are dependent on how the polymer is labeled and includes, for instance, all of the information

09928668.081301

described above as “unit specific information.” The presence or absence of a particular sequence can be established by determining whether any polymers within the sample express a characteristic pattern of individual units which is only found in the polymer of interest i.e., by comparing the detected signals to a known pattern of signals characteristic of a known polymer to determine the relatedness of the polymer being analyzed to the known polymer. The entire sequence of the polymer of interest does not need to be determined in order to establish the presence or absence of the polymer in the sample. Similarly the methods may be useful for comparing the signals detected from one polymer to a pattern of signals from another polymer to determine the relatedness of the two polymers.

In one example the structural information provides the length of the polymer. The lengths of polymers are most easily determined from labeling all of the units of the polymer. As the polymers migrate past their respective restrictive nanostructures in a linear fashion, the photon flux from each of the restricted polymers is determined. An example using a nucleic acid is illustrated in Figure 1-11 wherein the nucleic acid is drawn through small channels in a membrane in a linear fashion by electrophoresis. The nucleic acid is labeled throughout the strand. The nucleic acid is excited by fluorescence illumination. The blackened membrane does not permit excitation of molecules below the membrane. As the fluorescently labeled nucleic acid molecules migrate past the nonochannels, they are fixed spatially. Integration of the collected signal gives rise to discrete, spatially separated intensity spots on the fluorescence image. The intensity of the spots are directly proportional to the length of the nucleic acid molecules. After electrophoretic migration past the channels, the nucleic acid is drawn out of the imaging area by a displaced electrode. Experimental details are provided in the Examples below.

The determination of the length of the polymer can be performed on a single polymer if each unit of the polymer is labeled. If most of the units of a plurality of polymers in a sample are labeled on each unit and the method is performed on a plurality of identical polymers then by comparing the intensities of the entire population the length can be determined.

In another example the structural information provides the number of polymers passing through a restrictive nanostructure in a given amount of time. The number of polymers can be determined by labeling each polymer with a fixed number of fluorophores. This can be accomplished for example by phosphate end-labeling the polymers using kits



available from Molecular Probes. The brightness of the intensity spots in the analysis should be in fixed increments of two labels. A restrictive nanostructure with four polymers passing through it in a time (t) would give rise to an intensity spot of eight fluorophores.

In yet another example the structural information provides unit specific information about the polymer. In an example ssDNA are labeled with peptide nucleic acids (PNAs) which bind with high  $T_m$  to the desired and specific sequences. The PNAs are cross-linked to the single-stranded DNA through uv crosslinking and the formation of PNA-DNA covalent complexes. The labeled PNAs are detected in the restrictive nanostructures. Based on the brightness of the individual wavelengths corresponding to the different probes used, information about the composition of internal sequences of a strand in question can be determined.

An example of a restrictive structure which enables measurement of intensity signals at a fixed station is a nanostructure fabricated by e-beam lithography and reactive ion etching as shown in Figure 12. High resolution e-beam lithography is capable of fabricating structures with gap sizes on the order to 10 nm. These small structures can be used to restrict the movement of DNA. The structure shown in Figure 12 is nanofabricated from quartz by e-beam lithography and reactive ion etching. Preferably it is a waveguide with a metallic surface. Multicolor excitation at each of the waveguides is initiated to excite the individual DNA molecules. The surfaces of the substrate are cleaned by an oxygen plasma cleaner. The hydrophilic surfaces are wetted and the top of the structures are sealed with a coverslip spin coated with silicone (Newark Electronics, NJ). The DNA molecules are migrated through the structures electrophoretically. Intensity images of the molecules are obtained. The total photon count per molecule is proportional to the length of the molecule.

Another example of a restrictive nanostructure which may be used is a monolayer of hexagonally packed beads which has the configuration shown in Figure 13. The dimensions of the geometric areas between the beads can be easily calculated.

The methods of the invention can be used to identify one, some, or many of the units of the polymer. This is achieved by identifying the type of individual unit and its position on the backbone of the polymer by determining the intensity of a signal arising from the labeled polymer using labeled sequence specific probes as described in greater detail above.

In general the methods of linear polymer analysis using intensity are performed by detecting optical signals. An "optical signal" as used herein differs from a polymer dependent

impulse and is a detectable electromagnetic radiation signal which transmits or conveys information about the structural characteristics of a polymer and from which a quantitative analysis of intensity can be determined. The optical signal may arise from energy transfer, quenching, radioactivity, or any other physical changes from which a quantitative measure of

5 intensity can be derived. The signal preferably is optically detected. An "optically detectable" signal as used herein is a light based signal in the form of electromagnetic radiation which can be detected by light detecting imaging systems.

Optical detectable signals are generated, detected and stored in a database the signals can be analyzed to determine structural information about the polymer. The signals can be

10 analyzed by assessing the intensity of the signal to determine structural information about the polymer. The computer may be the same computer used to collect data about the polymers, or may be a separate computer dedicated to data analysis. A suitable computer system to implement the present invention typically includes an output device which displays information to a user, a main unit connected to the output device and an input device which

15 receives input from a user. The main unit generally includes a processor connected to a memory system via an interconnection mechanism. The input device and output device also are connected to the processor and memory system via the interconnection mechanism. Computer programs for data analysis of the detected signals are readily available from CCD manufacturers.

20 The methods of the invention can be accomplished using any device which produces a specific detectable polymer dependent impulse for an individual unit specific marker of a polymer. One type of device which enables this type of analysis is one which promotes linear transfer of a polymer past an interaction station or a signal generation station, such as, an article of manufacture including a wall material having a surface defining a channel, an agent

25 selected from the group consisting of an electromagnetic radiation source, a quenching source, a luminescent film layer, and a fluorescence excitation source, attached to the wall material adjacent to the channel. Preferably the agent is close enough to the channel and is present in an amount sufficient to detectably interact with a partner compound selected from the group consisting of a light emissive compound and a quencher passing through the

30 channel.

A wall material is a solid or semi-solid barrier of any dimensions which is capable of supporting at least one channel. A semi-solid material is a self supporting material and may

be for instance a gel material such as a polyacrylamide gel. For instance the wall material may be composed of a single support material which may be conducting or non-conducting, light permeable or light impermeable, clear or unclear. In some instances the agent is embedded within the wall material. In these instances the wall material can be solely or partially made of a non-conducting layer, a light permeable layer or a clear layer to allow the agent to be exposed to the channel formed in the wall material to allow signal generation. When the wall material is only partially made from these materials the remaining wall material may be made from a conducting, light impermeable or unclear layer, which prevent signal generation. In some cases the wall material is made up of layers of different materials. For instance, the wall material may be made of a single conducting layer and a single non-conducting layer. Alternatively the wall material may be made of a single non-conducting layer surrounded by two conducting layers. Multiple layers and various combinations of materials are encompassed by the wall material of the invention.

As used herein a "luminescent film layer" is a film which is naturally luminescent or made luminescent by some means of excitation or illumination, e.g., electrooptic thin films and high index films illuminated by internal reflection.

As used herein a "material shield" is any material which prevents or limits energy transfer or quenching. Such materials include but are not limited to conductive materials, high index materials, and light impermeable materials. In a preferred embodiment the material shield is a conductive material shield. As used herein a "conductive material shield" is a material which is at least conductive enough to prevent energy transfer between donor and acceptor sources.

A "conductive material" as used herein is a material which is at least conductive enough to prevent energy transfer between a donor and an acceptor.

A "nonconductive material" as used herein is a material which conducts less than that amount that would allow energy transfer between a donor and an acceptor.

A "light permeable material" as used herein is a material which is permeable to light of a wavelength produced by the specific electromagnetic radiation, quenching source, or the fluorescence excitation source being used.

A "light impermeable material" as used herein is a material which is impermeable to light of a wavelength produced by the specific electromagnetic radiation, quenching source, or the fluorescence excitation source being used.

A "channel" as used herein is a passageway through a medium through which a polymer can pass. The channel can have any dimensions as long as a polymer is capable of passing through it. For instance the channel may be an unbranched straight cylindrical channel or it may be a branched network of interconnected winding channels. Preferably the channel is a straight nanochannel or a microchannel. A "nanochannel" as used herein is a channel having dimensions on the order of nanometers. The average diameter of a nanochannel is between 1 nm and 999 nm. A "microchannel" as used herein is a channel having dimensions on the order of micrometers. The average diameter of a microchannel is between 1mm and 1mm. Preferred specifications and dimensions of channels useful according to the invention are set forth in detail below. In a preferred embodiment, the channel is fixed in the wall.

An agent is attached to the wall material in such a manner that it will detectably interact with a partner compound by undergoing energy transfer or quenching with the partner light emissive compound which is passing through the channel of the wall material. In order to interact with the partner compound the agent can be positioned in close proximity to the channel. For example, the agent may be attached to the inside of the channel, attached to the external surface of the wall material, attached to a concentrated region of the external surface of the wall material surrounding the rim of the channel, embedded within the wall material, or embedded in the form of a concentric ring in the wall material surrounding the channel.

Optionally the agent may cover the entire surface of the wall material or may be embedded throughout the entire wall material. In order to improve signal generation when the agent is not localized, a mask may be used to cover some areas of the wall material such that only localized regions of agent are exposed. A "mask" as used herein is an object which has openings of any size or shape. More than one agent may be attached to the wall material in order to produce different signals when the agents are exposed to the partner agent.

The agent may be attached to the surface of the wall material by any means of performing attachment known in the art. Examples of methods for conjugating biomaterials are presented in Hermanson, G. T., *Bioconjugate Techniques*, Academic Press, Inc., San Diego, 1996, which is hereby incorporated by reference.

When the agent is attached to the surface of the wall material it may be attached directly to the wall material or it may be attached via a linker. A "linker" as used herein with respect to the attachment of the agent is a molecule that tethers a light emitting compound or a

quenching compound to the wall material. Linkers are well known in the art. Commonly used linkers include alkanes of various lengths.

The agent is attached to the wall material in an amount sufficient to detectably interact with a partner light emissive compound. As used herein a “partner light emissive compound” is a light emissive compound as defined above but which specifically interacts with and undergoes energy transfer or quenching when positioned in close proximity to the agent. The amount of partner light emissive compound and the amount of agent required will depend on the type of agent and light emissive compound used.

Another example of an article of manufacture which is useful for practicing the method of the invention is a wall material having a surface defining a plurality of channels and a station attached to a discrete region of the wall material adjacent to at least one of the channels, wherein the station is close enough to the channel and is present in an amount sufficient to cause a signal to arise from a detectable physical change in a polymer of linked unit specific markers passing through the channel or in the station as the polymer is exposed to the station. A “discrete region” of the wall material adjacent to at least one of the channels is a local area which is surrounded by wall material not having a station. The area surrounding the discrete region does not interact with the unit specific marker to produce the same characteristic signal produced by the interaction of the unit specific marker with the station. The discrete region is positioned in or near the channel such that the station at the discrete region is exposed to the unit specific marker as it traverses the channel.

An additional article of manufacture useful for practicing the method of the invention is a wall material having a surface defining a channel and a plurality of stations each attached to a discrete region of the wall material adjacent to the channel, wherein the stations are close enough to the channel and are present in an amount sufficient to cause a signal to arise from a detectable physical change in a polymer of linked unit specific markers passing through the channel or in the station as the polymer is exposed to the station.

As used herein a “plurality of stations” is at least two stations. Preferably a plurality of stations is at least three stations. In another preferred embodiment a plurality of stations is at least five stations.

PCT Patent Application PCT/US98/03024 provides a detailed description of an optimal design of a nanochannel plate having fluorophores embedded within the plate as well as other articles useful for practicing the methods of the invention. The methods of the invention are

not limited, however, to the use of articles of manufacture described herein or in the priority PCT application. The examples are provided for illustrative purposes only. The methods of the invention can be performed using any system in which a plurality of unit specific markers of a polymer can be moved with respect to a fixed station and from which signals can be

5 obtained.

A preferred method of the invention involves the analysis of radiolabeled polymers as discussed above. Preparation of radiolabeled polymers such as DNA (for example, with  $^{32}\text{P}$  or  $^3\text{H}$ ) is known in the art. The following description represents one of the many possible embodiments of analyzing radiolabeled polymers according to the methods of the invention.

10 A radiolabeled nucleic acid molecule is analyzed with a single fabricated multilayered nanochannel. The nanochannel is the diameter of the labeled nucleic acid molecule and is constructed to yield a defined region of detection. Exemplary nanochannel plates include a heterogeneous multilayered structure consisting of two radiation impermeable layers such as lead or Lucite films and a film of lower density material (or scintillation layer) (i.e.,  
15 conventional polymers, polymethylmethacrylate, polystyrene, Teflon, etc.). The lead films sandwich the layer of lower density material and are of such thickness as to prevent passage of radiation. The lower density material permits passage of radiation, thereby creating a defined region of radiation detection. As the radiolabel on the DNA passes through the  
20 defined region of radiation detection, nuclear radiation is emitted, some of which will pass through the defined region of radiation detection.

In a related embodiment of analysis of radiolabeled nucleotides a detection system based on scintillation counting and multiple nanochannels is presented. A nanochannel array is fabricated. Multiple multilayered channels exist for parallel amplification of data output. Each individual channel consists of two nuclear radiation shielding layers which shield  
25 nuclear radiation, and a scintillation layer which is fluorescently excited with exposure to nuclear radiation. The individual channels are separated from each other by a nuclear radiation shielding material. The nuclear radiation is prevented from reaching the fluorescent detection system by overlaying with optical quality Lucite (or any other transparent material which prevents the passage of nuclear radiation). This allows only the fluorescent signal to  
30 reach the detection system.

Each of the above described nanochannels is only an example. It is, therefore, anticipated that each of the limitations described with respect to these embodiments involving

any one element or combinations of elements can be included in each nanochannel. Preparation of films having multiple layers of differing material have been described in the art, e.g., US Patent No. 5,462,467, Ferreira et. al., *Thin Solid Films* 244:806-809 (1994).

In one embodiment the signal station is fixed. A station is "fixed" as used herein if the station and the detection device do not move. The polymer may move past the fixed station but the station does not move. In one embodiment the station is an interaction station. As used herein an "interaction station or site" is a region where a unit specific marker of the polymer interacts with an agent and is positioned with respect to the agent in close enough proximity whereby they can interact. The interaction station for fluorophores, for example, is that region where they are close enough so that they energetically interact to produce a signal.

Methods for preparing the wall material and the various light conductive and non-conductive layers etc are described in co-pending PCT Patent Application PCT/US98/03024.

An example of an apparatus constructed to hold a nanochannel (or microchannel) plate which is capable of generating an electric field is described. The electric field, created by electrodes, is used to draw the DNA through the nanochannels. The exemplary nanochannel plate is immersed in a slightly viscous buffer solution which helps to slow the transit of the polymer through the nanochannel, so as to allow for a longer signal collection time per base. In addition, on either side of the plate are electrodes immersed in the buffer solution. The ensemble of nanochannel plate, buffer compartments, and electrodes are contained in an optical quality glass chamber suitable for image analysis and are positioned adjacent to a 60x1.4NA oil objective.

As discussed above the use of an electric field to cause the polymer to move linearly through a channel is preferred. The use of an electric field is suitable because the stretched, linear orientation of a polymer in an electric field is favorable for linear crossing of nanochannels. Furthermore, the rate of polymer movement can be controlled by voltage. Lastly, an electric field does not adversely affect FRET.

Light microscopy (Bustamante, 1991; Gurrieri et al., 1990; Matsumoto et al., 1981, Rampino and Chrambach, 1990; Schwartz and Koval, 1989; Smith et al., 1989), linear dichroism (LD) (Åkerman et al., 1990; Åkerman et al., 1985, Moore et al., 1986), fluorescence-detected LD (Holzwarth et al., 1987), and linear birefringence (Sturm and Weill, 1989; Chu et al., 1990) can be used to study the instantaneous changes in shape of DNA

molecules undergoing gel electrophoresis. In these studies DNA is shown to be strongly oriented and stretched.

Guirrieri et al., 1990 has demonstrated linear and stretched conformation of DNA molecules in an electric field. In each of the cases, the DNA molecule is clearly aligned in the direction of the applied electric field. The method used to visualize the DNA molecules combines fluorescent DNA labeling and use of an image intensifier-video camera system (Bustamante, 1991; Houseal et al., 1989; Morikawa and Yanagida, 1981; Matsumoto et al., 1989; Yanagida et al., 1983). The DNA molecules shown are T2 molecules which are 164 kbp long.

The orientation of DNA in an electric field has been well studied with linear dichroism and electric dichroism (Ding et al., 1972; Yamaoka and Charney, 1973; Colson et al., 1974; Hogan et al., 1978; Priore and Allen, 1979; Yamaoka and Matsuda, 1981; Wu et al., 1981). In fact, the first studies done on DNA orientation have been performed with these two techniques. DNA was first studied in solution and then subsequently in electrophoretic gels. Studies both in solution and in gels yield similar results in that the DNA molecules are indeed oriented in the direction of the electric field.

The invention in another aspect is a kit for labeling polymers. The kit includes a container housing a series of distinct nucleic acid probes; wherein the series of nucleic acid probes is a set of multiple base pair probes. Preferably the multiple base pair probes are selected from the group consisting of two base pair probes, three base pair probes, four base pair probes, and five base pair probes, but may be any number of base pairs greater than one.

A "base pair probe" as used herein refers to a single stranded nucleic acid fragment that can be used to hybridize to an unknown sequence. The term is used consistently with its common meaning in the art. A "set of multiple base pair probes" as used herein is a series of base pair probes of a specific length, wherein the series of probes includes each possible combination of nucleic acid sequences of that particular length. For any given number of nucleic acid sequences, the number of different base pair probes which can be used is defined by the formula  $4^n$ , where  $n$  is the number of nucleic acid sequences. For instance a two base pair probe, which spans two nucleotides, would include 16 combinations of nucleotide pairs. These include, AC, AG, AT, AA, CC, CA, CG, CT, GA, GG, GC, GT, TA, TC, TG, and TT. A three base pair probe, which spans three nucleotides, would include a combination of 54



three nucleotide pairs combinations. Those of ordinary skill in the art would easily be able to identify each of the different combinations.

In one embodiment the container is a single container having a plurality of compartments, each housing a specific labeled probe. In another embodiment the container is a plurality of containers. An example of a kit is presented in Figure 10.

The kit in one embodiment also includes instructions for labeling the nucleic acid probes, if the probes are not already labeled.

The distinct nucleic acid probes are labeled in one embodiment. Preferably the nucleic acid probes are labeled with an agent selected from the group consisting of an electromagnetic radiation source, a quenching source and a fluorescence excitation source. In one embodiment the plurality of polymers is a homogenous population. In another embodiment the distinct nucleic acid probes are three base pair probes. In another embodiment the distinct nucleic acid probes are four base pair probes. In yet another embodiment the distinct nucleic acid probes are five base pair probes.

#### Examples

**Example 1:** The DNA solution is prepared by mixing together with TOTO-1 obtained from Molecular Probes, OR. TOTO-1 is a dimeric cyanine dye which is virtually nonfluorescent in the absence of binding to dsDNA. Upon binding the fluorescence is increased over 1000-fold. Excitation of the dye is at 514 nm and emission is at 533. Nanomolar concentrations of the dye is used in 0.5x TBE buffer. The polycarbonate membrane are blackened by dissolving 2 gm of Irgalan black (Chemical Index, acid black 107) in 1 L of 2% acetic acid. Membranes are soaked in Irgalan black solution for 24 hours. The samples are rinsed with water and dried in air. The membrane is mounted in a dual buffer compartment which has an optical window for collecting fluorescence images. An electric field between 1 V/cm to 20 V/cm is used to electrophoretically drive the DNA through the nanochannels which can range in diameter of 5 nm to 10 nm. DNA crossing the nanochannels non-linearly would give aberrant intensity signals which, upon statistical average, would give rise to noise.

The foregoing written specification is considered to be sufficient to enable one skilled in the art to practice the invention. The present invention is not to be limited in scope by examples provided, since the examples are intended as a single illustration of one aspect of the invention and other functionally equivalent embodiments are within the scope of the invention. Various modifications of the invention in addition to those shown and described

herein will become apparent to those skilled in the art from the foregoing description and fall within the scope of the appended claims. The advantages and objects of the invention are not necessarily encompassed by each embodiment of the invention.

All references, patents and patent publications that are recited in this application are  
5 incorporated in their entirety herein by reference.

I claim:

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
22